

4G V-Station Lite™

Features at a glance:

- Full color 1.5 inch LCD screen
- Single, Dual or Multi-Factor Authentication; Finger only / Card+ Finger / Card + Finger + PIN (Prox, iCLASS, MIFARE, DESFire)
- Large template storage capacity (5,000 in 1:N; 25,000 in 1:1)
- Integrated PIN pad and 3 navigation keys
- 500 DPI optical fingerprint sensor ensures high quality templates
- IP connectivity
- IP65 rating allows indoor and outdoor capabilities
- Tamper Detection
- Log capacity of 100,000 logs

Powerful Features in a Compact Design

The 4G V-Station Lite™ is a slim yet powerful device which captures the technological brilliance of our 4G V-Station™ and the small form factor design of our 4G V-Flex Lite™.



After careful research into customers' feedback, we designed the 4G V-Station Lite™ to streamline installation and administration for small, medium or large business enterprise, or for standalone door access control deployment. The new design brings the high speed, accuracy and interactivity of a 4G V-Station™ to the small form factor of the 4G Lite™ suite of products.

4G V-Station Lite™

Product Specifications

Dimensions	Height: 8.86" (225 mm) Width: 2.05" (52 mm) Depth: 2.00" (51 mm)
Network Communication Options	Ethernet (TCP/IP) and RS485 PC Connection: USB
Flash Memory	256MB
Input/Output	<ul style="list-style-type: none"> • Option for Wiegand in/out (512 bit) • 2 General Purpose Input (REX, Door Contact) • 1 Form C Relay Output • 1 General Purpose Output
Integrated Door Relay Details	30 VDC @ 1A Deadbolt, electromagnetic (EM) lock, door strike, automatic door
Authentication Options	Finger Only Finger + PIN Card Only Card + Finger Card + PIN Card + Finger + PIN
Template Capacity	1:N 5,000 1:1 25,000
Internal Card Reader Options	4G V-Station Lite Base: N/A 4G V-Station Lite Prox: HID Proximity Reader 4G V-Station Lite Smart: HID Omnikey 6321 iCLASS/MIFARE/DESFire Card Reader
Audio	Supports .wav custom files
Transaction Log Capacity	100,000 transaction logs stored on device
Voltage	12-24V DC
Current Draw	500 mA @ 12 VDC
Environmental Specs	-5°F to 150°F (-20°C to 65°C) IP 65 Rated
Regulatory Approvals and Certifications	FCC, CE, R&TTE, RoHS, IP 65

Device Models:

4G V-Station Lite™ is available in 2 model variants, with Wiegand output and with No Wiegand output (NW). The (NW) device models are designed for single door access control, removing the requirements for access panels and Wiegand communication. All door relay, door contact and request to exit capabilities are integrated into the devices. 4G SecureControl can also be used with all 4G V-Station Lite™ products.

About Bioscrypt

With over 450,000 readers deployed in over 90 countries, Bioscrypt protects and secures identities and assets by helping customers address demanding access control and identity authentication requirements with innovative and reliable systems.

Our Advantage:

- One of the most established companies that specialize in biometric access control solutions.
- Market-tested and customer proven solutions that are interoperable, and designed to grow with you.
- Knowledgeable technical support team ready to help answer your questions and get you up and running.

Contact Us:

Global

Sales-EnterpriseAccess@L1ID.com
800 444 0496 • 905 940 7490

Offices

Canada • United States

www.L1ID.com/EnterpriseAccess

Copyright © 2011, L-1 Identity Solutions, Inc. All rights reserved. The trademarks identified herein are the trademarks or registered trademarks of L-1 Identity Solutions, Inc. or other third party.

Call or email us to [Schedule](#) an appointment today for a solution overview and demo.